

TUGOPSA LJ AUTOMATED VALVE TLJ2015A6/8

NEEDLE TYPE SURFACE VALVE WITH
INTERNALS ALLOWING FREE AND
ARTICULATE MOVEMENT

DATA SHEET

PARTS	MATERIALS
BODY	AISI-SAE 1020
COUPLING	AISI-SAE 304
STEM	AISI –SAE 304
BOX	AISI-SAE 1020
NEEDLE	AISI –SAE 304
SEAT	AISI –SAE 304
SADDLE	AISI-SAE 1020
VISOR SCREW	SAE 430 B BF
VISOR	SAE 430 B BF
VISOR PIN	AISI –SAE 304
PACKINGS	VITON , TEFLON
SCREWS	AISI-SAE 304



APPLICATIONS


WITH THE IDEAL STANDARD TRIM TO CONTROL INJECTION OF DILUENTS SUCH AS: EXTRA-LIGHT CRUDES, NAPHTA AND GAS

WORKING CONDITIONS

WORKING PRESSURES	150 - 600 PSI
MAXIMUM TEMPERATURES	-40 °F – 150 °F
CONNECTION	WAFFER

DIMENSIONS

WIDTH	LOWER: 3.89 in UPPER: 9.20 in
LENGTH	18.10 in
DEPTH	LOWER: 2.99 in UPPER : 8.20 in



WEIGHT:
25.79 Lb