

TUGOPSA LJ MANUAL VALVE TLJ2015M6/8

NEEDLE TYPE SURFACE VALVE WITH
INTERNALS ALLOWING FREE AND
ARTICULATE MOVEMENT

DATA SHEET



PARTS	MATERIALS
BODY	AISI-SAE 1020
COUPLING	AISI-SAE 304
STEM	AISI –SAE 304
BOX	AISI-SAE 1020
NEEDLE	AISI –SAE 304
SEAT	AISI –SAE 304
SADDLE	AISI-SAE 1020
VISOR SCREW	SAE 430 B BF
VISOR	SAE 430 B BF
VISOR PIN	AISI –SAE 304
PACKINGS	VITON , TEFLON
SCREWS	AISI-SAE 304

APPLICATIONS

WITH THE IDEAL STANDARD TRIM TO
CONTROL INJECTION OF DILUENTS SUCH
AS: EXTRA-LIGHT CRUDES, NAPHTHA AND
GAS

WORKING CONDITIONS

WORKING PRESSURES	150 - 600 PSI
MAXIMUM TEMPERATURES	-40 °F – 150 °F
CONNECTION	WAFFER

DIMENSIONS

WIDTH	99 mm
LENGTH	267.05 mm
DEPTH	76 mm

